



Product Overview:
11 different
electro-chemical Systems

RECHARGEABLE MICRO BATTERIES

VARTA Microbattery combines entrepreneurial substance, strategic visions and technological competency for constantly improved products, application oriented designs and innovative product development. For more information please visit our internet page www.varta-microbattery.com.

Type Designation	Type No.	Voltage (V)	Capacity (mAh)	Diameter (mm)	Height (mm)	Length (mm)	Width (mm)	Weight (g)
------------------	----------	-------------	----------------	---------------	-------------	-------------	------------	------------

Rechargeable Ni-MH Battery Range

Rechargeable Button Cells (Ni-MH)

V...H robust								
V 15 H	55602	1.2	16	11.5	3.1			1.3
V 40 H	55604	1.2	43	11.5	5.35			1.7
V 80 H	55608	1.2	80	15.5	6.0			4.0
V 150 H	55615	1.2	150		5.85	14.1	25.6	6.0
V 200 H	55620	1.2	210		7.4	14.1	25.6	7.0
V 250 H	55625	1.2	250	25.1	6.7			10.0
CP 300 H	55630	1.2	300	25.1	7.55			11.0
V 350 H	55635	1.2	380	25.1	8.8			13.0
V...HT robust85C								
V 65 HT	55707	1.2	70	15.5	6.0			4.0
V 110 HT**	55711	1.2	120		5.85	14.1	25.6	6.0
V 150 HT	55715	1.2	150		5.85	14.1	25.6	6.0
V...HR powerful								
V 6 HR	55996	1.2	6.2	6.8	2.15			0.28
V 450 HR	55945	1.2	450		5.6	24.1	34.1	12.5
V 600 HR	55960	1.2	600		6.8	24.1	34.1	14.5
V...HRT powerful85C								
V 18 HRT	55802	1.2	19	11.5	2.3			0.9
V 500 HRT	55850	1.2	510		6.6	24.2	34.1	14.0
V 500 H(R)T	55750	1.2	510		6.6	24.2	34.1	14.0
V 650 HRT	55865	1.2	650		6.8	24.2	34.1	15.0
RTC/MBU								
RTC 6	55997	1.2	6.2	6.8	2.15			0.28
MBU 20	55803	1.2	19	11.5	2.3			0.9

* 0° - 65°C

Not all product types are available at the time of printing.

Voltage and Capacity indicated refer to nominal and typical values respectively.

Rechargeable Cylindrical Cells (Ni-MH)

VH 700 AAA	55171	1.2	730	10.5	43.7			13.0
VH 1300 AA	55115	1.2	1340	14.4	48.2			25.0
VH 1600 AA	55119	1.2	1640	14.5	49.2			26.0
VH 1800 AA	55123	1.2	1850	14.5	49.2			27.0
VH 2050 4/5A	55021	1.2	2050	17.0	43.0			32.0
VH 2650 A	55027	1.2	2650	17.0	50.0			39.5
VH 3750 4/3A	55038	1.2	3750	17.5	67.0			53.5
VH 4400 4/3 FA	55044	1.2	4400	18.3	67.0			60.0
High Capacity Range								
VH 2100 4/5A	55118	1.2	2150	17.0	43.0			35.0
VH 2700 A	55127	1.2	2700	16.7	48.8			40.0
VH 4000 4/3A	55140	1.2	4000	17.0	67.5			55.0
VH 4500 4/3 FA	55145	1.2	4500	18.0	67.5			58.0

9V Batterie (Ni-MH)

V 7/8 H	05122	8.4	180		15.7	48.5	26.6	48.0
V 6/8 H	05422	7.2	150		15.7	48.5	26.6	41.0
V 7/8 H	05522	8.4	150		15.7	48.5	26.6	47.0
V 7/8 H	05622	8.4	150		15.7	48.5	26.6	47.0
V 6/8 H	05722	7.2	175		15.7	48.5	26.6	41.0

Type Designation	Type No.	Voltage (V)	Capacity (mAh) Standard version	Diameter (mm)	Height (mm)	Length (mm)	Width (mm)	Weight (g)
------------------	----------	-------------	---------------------------------	---------------	-------------	-------------	------------	------------

Rechargeable Lithium Battery Range

Rechargeable Prismatic and Cylindrical Cells

Li-Polymer/Li-Ion Pouch-Types								
LPP 402025 CE	56416	3.7	150		4.3	25.5	20.5	3.7
LPP 402934 E	56417	3.7	310		4.0	34.2	29.2	3.7
LPP 422339 PL	56477	3.7	380		4.1	39.5	23.5	7.5
LPP 383450 8TH	56428	3.7	830		3.85	50.0	34.0	14.3
LPP 473350 8TH	56479	3.7	970		4.7	50.0	33.0	17.1
LPP 523450 DL	56493	3.7	1000		5.4	50.5	34.5	17.0
LPP 383759 9HH	56440	3.7	1010		3.85	59.0	37.0	18.0
LPP 423566 BE	56437	3.7	1160		4.2	65.4	35.0	25.0
LPP 453759 9HH	56438	3.7	1260		4.5	59.0	37.0	21.0
LPP 503562 DL	56422	3.7	1300		5.2	62.5	35.5	21.0
LPP 503759 DL	56478	3.7	1300		5.2	59.5	37.5	23.0
LPP 503759 8HH	56427	3.7	1400		5.0	59.0	37.0	23.6
LPP 454261 8TH	56426	3.7	1590		4.6	61.0	42.0	27.3
LPP 683566 BE	56432	3.7	1880		6.7	65.4	35.0	33.0
Li-Ion Can-Types								
LIP 423048 AJL	56476	3.7	720		4.5	48.0	29.8	15.1
LIP 533048 AJ	56466	3.7	740		5.3	47.8	30.0	17.0
LIP 423450 AJL	56424	3.7	880		4.5	50.0	34.2	18.0
LIP 553450 WC	56441	3.7	1130		5.5	50.0	34.0	23.0
LIP 523450 AJL	56425	3.7	1100		5.5	49.8	33.8	23.0
LIP 653450 UC	56491	3.7	1230		6.6	50.0	34.0	25.5
LIP 103450 SC	56429	3.7	2030		10.5	48.7	33.9	42.0
Li-Ion Round-Types								
LIC 18650 22FC	56621	3.7	2200	18.4	65.0			44.0
LIC 18650 22L	56622	3.7	2200	18.4	65.1			48.0
LIC 18650 24FC	56624	3.7	2400	18.4	65.0			46.0
LIC 18650 26CC	56626	3.7	2600	18.4	65.0			47.0

Rechargeable Lithium-Polymer/Standard Battery Packs

EasyPack, 3.7 V									
EZPack S-3.7V	66590	711	099	610		6.0	43.7	35.6	14.0
EZPack L-3.7V	66383	711	099	1320		6.6	64.7	36.8	25.0
EZPack XL	66380	712	099	2000		11.6	64.7	36.8	46.5
EZPack XL-3.7V	66383	712	096	2640		11.6	64.7	36.8	46.5

Rechargeable Lithium Button Cells (Li-Ion)

ML 1220	65013	3.0	16.0	12.5	2.0			1.0
---------	-------	-----	------	------	-----	--	--	-----

PRIMARY MICRO BATTERIES

Small, in many cases invisible, microbatteries reliably supply a wide variety of devices with energy. Without microbatteries, many of the products surrounding us would only be possible in much more complex forms, if at all, and would therefore also be much more difficult to handle.

Type Designation	Type No.	Voltage (V)	Capacity (mAh)	Diameter (mm)	Height (mm)	Length (mm)	Width (mm)	Weight (g)
------------------	----------	-------------	----------------	---------------	-------------	-------------	------------	------------

Card Power Lithium Cells (Li-MnO₂)

LFP 25	6804	3.0	25.0		0.44	22.0	29.0	0.6
--------	------	-----	------	--	------	------	------	-----

Lithium Cylindrical Cells (Li-MnO₂)

CR mass/bobbin series								
CR 1/2 AA	6127	3.0	950	14.75	25.1			11.5
CR 2/3 AA	6237	3.0	1350	14.75	33.5			15.0
CR AA	6117	3.0	2000	14.75	50.5			21.5
CR coiled series								
CR 2/3 AH	6215	3.0	1500	17.0	33.5			17.0
CR 123 A	6205	3.0	1550	17.0	34.5			17.0
CR 2	6206	3.0	850	15.6	27.0			11.0

Lithium Button Cells (Li-MnO₂)

CR 1216	6216	3.0	27	12.5	1.6			0.7
CR 1220	6220	3.0	35	12.5	2.0			0.8
CR 1616	6616	3.0	55	16.0	1.6			1.2
CR 1620	6620	3.0	70	16.0	2.0			1.2
CR 2016	6016	3.0	90	20.0	1.6			1.8
CR 2025	6025	3.0	165	20.0	2.5			2.5
CR 2032	6032	3.0	230	20.0	3.2			3.0
CR 2430	6430	3.0	280	24.5	3.0			4.0
CR 2450	6450	3.0	560	24.5	5.0			6.2
CR 1/3 N	6131	3.0	170	11.6	10.8			3.0
P 28 PXL	6231	6.0	170	13.0	25.1			8.8

Alkaline Manganese Button Cells (Zn-MnO₂)

V 10 GA	4274	1.5	50	11.6	3.05			1.1
V 12 GA	4278	1.5	70	11.6	4.2			1.35
V 13 GA	4276	1.5	125	11.6	5.4			1.8
P 23 GA	4223	12.0	50	10.3	28.5			7.5
V 625 U	4626	1.5	200	15.5	6.1			3.3

powerone Alkaline Cylindrical Cells

LR 03								
Micro/AAA/AM 4	4103	1.5	1.200	10.5	44.5			11
LR 6								
Mignon/AA/AM 3	4106	1.5	2.600	14.5	50.5			23
LR 14								
Baby/C/AM 2	4114	1.5	7.800	26.0	50.0			69
LR 20								
Mono/D/AM 1	4120	1.5	16.500	34.0	61.0			141
6 LR 61								
E-Block/6 AM 6	4122	9	550	48.5	26.5		17.5	46





Type Designation	Type No.	Type Designation Mercury-Free	Type No. Mercury-Free	Voltage (V)	Capacity (mAh) Standard version	Diameter (mm)	Height (mm)	Weight (g)
------------------	----------	-------------------------------	-----------------------	-------------	---------------------------------	---------------	-------------	------------



Silver Oxide Button Cells (Ag₂O)

V 301	301	V 301 MF	20 301	1.55	115	11.6	4.2	1.78
V 303	303	V 303 MF	20 303	1.55	155	11.6	5.4	2.33
V 309	309	V 309 MF	20 309	1.55	70	7.9	5.4	1.08
V 315	315	V 315 MF	20 315	1.55	19	7.9	1.65	0.33
V 317	317	V 317 MF	20 317	1.55	10.5	5.8	1.6	0.18
V 319	319	V 319 MF	20 319	1.55	21	5.8	2.7	0.29
V 321	321	V 321 MF	20 321	1.55	14.5	6.8	1.65	0.25
V 329	329	V 329 MF	20 329	1.55	37	7.9	3.1	0.6
V 335	335			1.55	6	5.8	1.25	0.15
V 337	337			1.55	8.3	4.8	1.65	0.13
V 339	339			1.55	11	6.8	1.45	0.21
V 341	341			1.55	15	7.9	1.45	0.28
V 344	344			1.55	100	11.6	3.6	1.49
V 346	346			1.55	10	7.9	1.29	0.3
V 350	350			1.55	100	11.6	3.6	1.49
V 357	357	V 357 MF	20 357	1.55	145	11.6	5.4	2.33
V 361	361	V 361 MF	20 361	1.55	18	7.9	2.1	0.4
V 362	362	V 362 MF	20 362	1.55	21	7.9	2.1	0.4
V 364	364	V 364 MF	20 364	1.55	17	6.8	2.15	0.33
V 370	370	V 370 MF	20 370	1.55	34	9.5	2.1	0.6
V 371	371	V 371 MF	20 371	1.55	34	9.5	2.1	0.61
V 373	373	V 373 MF	20 373	1.55	29	9.5	1.65	0.5
V 377	377	V 377 MF	20 377	1.55	24	6.8	2.6	0.39
V 379	379	V 379 MF	20 379	1.55	14	5.8	2.15	0.23
V 381	381	V 381 MF	20 381	1.55	45	11.6	2.1	0.9
V 384	384	V 384 MF	20 384	1.55	38	7.9	3.6	0.69
V 386	386	V 386 MF	20 386	1.55	105	11.6	4.2	1.78
V 389	389	V 389 MF	20 389	1.55	81	11.6	3.05	1.31
V 390	390	V 390 MF	20 390	1.55	74	11.6	3.05	1.32
V 391	391	V 391 MF	20 391	1.55	40	11.6	2.1	0.9
V 392	392	V 392 MF	20 392	1.55	38	7.9	3.6	0.69
V 393	393	V 393 MF	20 393	1.55	70	7.9	5.4	1.08
V 394	394	V 394 MF	20 394	1.55	65	9.5	3.6	1.04
V 395	395	V 395 MF	20 395	1.55	42	9.5	2.7	0.75
V 396	396	V 396 MF	20 396	1.55	25	7.9	2.6	0.55
V 397	397	V 397 MF	20 397	1.55	24	7.9	2.6	0.5
V 399	399	V 399 MF	20 399	1.55	41	9.5	2.7	0.75
V 76 PX	4075			1.55	145	11.6	5.4	2.4

Product Portfolio

Primary Batteries					
	VARTA CardPower (Li-Polymer)		Lithium Cylindrical Cells		Zinc Air Cells
	Alkaline Batteries		Lithium Button Cells		Silver Oxide Button Cells
Rechargeable Batteries					
	Li-Polymer		Ni-MH Button Cells (V...H / HR / HT / HRT)		Cylindrical & Prismatic Li-Ion & Ni-MH Cells

Global Contacts

Germany and Central Europe
VARTA Microbattery GmbH
 Daimlerstraße 1
 73479 Ellwangen, Germany
 Tel +49 79 61 921 - 0
 Fax +49 79 61 921 - 553

China

Hongkong
 VARTA Microbattery Pte. Ltd.
 Room 1702-3, 17/F., Fullerton Centre
 19 Hung to Road, Kwun Tong
 Kowloon, Hongkong
 Tel +852 28 98 83 73
 Fax +852 28 97 76 09

Beijing

VARTA Microbattery Pte. Ltd.
 Room 05, 11/F., Xinyi Commercial Building
 3A Xinyijiayuan, Chongwenmenwai Avenue
 Chongwen District, Beijing
 China 100062
 Tel +86 10 67 09 60 57, 67 09 60 58
 Fax +86 10 67 09 60 59

Shanghai

VARTA Microbattery (Shanghai) Co. Ltd.
 Block 3, Shanghai Pudong Chuansha
 Industrial Park
 No. 6999 Chuansha Road
 Pudong New Area
 201202 Shanghai, China
 Tel +86 21 58 59 83 85
 Fax +86 21 58 59 33 13

Asia Pacific

VARTA Microbattery Pte. Ltd.
 300, Tampines Avenue 5, #05-01
 Tampines Junction, 529653 Singapore
 Tel +65 6 260 58 01
 Fax +65 6 260 58 12

Japan

VARTA Microbattery Pte. Ltd.
 Kyobashi Y'SUS Bldg, 3F.
 1-6-12, Kyobashi, Chuo-Ku
 Tokyo 104-0031, Japan
 Tel +81 3 35 67 81 71
 Fax +81 3 35 67 81 75

Taiwan

VARTA Microbattery Pte. Ltd.
 11F-4, No.130, Section 2
 Chung Hsiao East Road
 Taipei 10053, Taiwan
 Tel +886 2 33 93 15 57
 Fax +886 2 33 93 15 56

America

VARTA Microbattery, Inc.
 1311 Mamaroneck Avenue, Suite 120
 White Plains, NY 10605, USA
 Tel +1 914 592 25 00
 Fax +1 914 345 04 88

UK and Ireland

VARTA Microbattery GmbH
 17 Progress Business Centre,
 Whittle Parkway, Slough SL 1 6DQ, GB
 Tel +44 16 28 60 79 30
 Fax +44 16 28 60 79 39

France

VARTA Microbattery SARL
 12 - 14, Rue Raymond RIDEL
 92250 La Garenne Colombes, France
 Tel +33 1 47 84 84 54
 Fax +33 1 47 84 28 32

Distributors Internet

Distributors and representations in all major countries world wide. Consult our Webpage.
 For e-mail contact please visit: <http://contact.varta-microbattery.com>
 For more information please visit our website: www.varta-microbattery.com

VARTA Microbattery is a Company of
 Montana Tech Components AG,
 Hauptstrasse 35, 5737 Menziken, Switzerland

MONTANA
 TECH COMPONENTS